UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/611,948	07/03/2003	Hisashi Ishikawa	00862.023127.	5415
5514 7590 09/14/2010 FITZPATRICK CELLA HARPER & SCINTO 1290 Avenue of the Americas			EXAMINER	
			VO, QUANG N	
NEW YORK, NY 10104-3800			ART UNIT	PAPER NUMBER
			2625	
			MAIL DATE	DELIVERY MODE
			09/14/2010	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)
	10/611,948	ISHIKAWA, HISASHI
Office Action Summary	Examiner	Art Unit
	Quang N. Vo	2625
The MAILING DATE of this communication ap Period for Reply	ppears on the cover sheet with t	he correspondence address
A SHORTENED STATUTORY PERIOD FOR REP WHICHEVER IS LONGER, FROM THE MAILING I - Extensions of time may be available under the provisions of 37 CFR 1 after SIX (6) MONTHS from the mailing date of this communication.  - If NO period for reply is specified above, the maximum statutory perior Failure to reply within the set or extended period for reply will, by statu. Any reply received by the Office later than three months after the mail earned patent term adjustment. See 37 CFR 1.704(b).	DATE OF THIS COMMUNICATION 1.136(a). In no event, however, may a reply d will apply and will expire SIX (6) MONTHS ate, cause the application to become ABAND	TION. be timely filed from the mailing date of this communication. DONED (35 U.S.C. § 133).
Status		
Responsive to communication(s) filed on <u>15.</u> This action is <b>FINAL</b> . 2b) ☑ The Since this application is in condition for allow closed in accordance with the practice under	is action is non-final. ance except for formal matters	
Disposition of Claims		
4)  Claim(s) 1,3-7,20,22-26 and 39 is/are pendin 4a) Of the above claim(s) is/are withdr 5)  Claim(s) is/are allowed. 6)  Claim(s) 1,3-7,20,22-26 and 39 is/are rejecte 7)  Claim(s) is/are objected to. 8)  Claim(s) are subject to restriction and/	rawn from consideration.	
Application Papers		
<ul> <li>9) The specification is objected to by the Examir</li> <li>10) The drawing(s) filed on is/are: a) ac</li> <li>Applicant may not request that any objection to the Replacement drawing sheet(s) including the corre</li> <li>11) The oath or declaration is objected to by the Examir</li> </ul>	ccepted or b) objected to by the drawing(s) be held in abeyance. ection is required if the drawing(s) in	See 37 CFR 1.85(a). s objected to. See 37 CFR 1.121(d).
Priority under 35 U.S.C. § 119		
12) Acknowledgment is made of a claim for foreign a) All b) Some * c) None of:  1. Certified copies of the priority document 2. Certified copies of the priority document 3. Copies of the certified copies of the pri application from the International Bure * See the attached detailed Office action for a list	nts have been received. nts have been received in Appl iority documents have been rec au (PCT Rule 17.2(a)).	ication No ceived in this National Stage
Attachment(s)	Λ Π Inter-time 2	mary (DTO 412)
<ol> <li>Notice of References Cited (PTO-892)</li> <li>Notice of Draftsperson's Patent Drawing Review (PTO-948)</li> <li>Information Disclosure Statement(s) (PTO/SB/08)         Paper No(s)/Mail Date     </li> </ol>	Paper No(s)/M	mary (PTO-413) ail Date nal Patent Application

#### **DETAILED ACTION**

A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 7/15/2010 has been entered.

# Response to Arguments

Regarding claim 1, applicant's argument is not seen to disclose or to suggest at least the features of i) a bit connection component that connects a decimal portion of image data of a preceding pixel output from a latch component, to image data of a target pixel as lower bits of the image data of the target pixel, and outputs the bit-connected image data of the target pixel, wherein the bit-connected image data has an integer portion of the image data of the target pixel and the decimal portion of image data of the preceding pixel, ii) a latch component that latches a decimal portion of the corrected image data of the target pixel to be connected to image data of a next pixel, without latching an integer portion of the corrected image data of the target pixel, iii) a quantization component that receives an integer portion of the corrected image data without receiving the decimal portion of the corrected image data of the target pixel, and quantizes the received integer portion of the corrected image data of the target pixel, and iv) an error diffusion component that generates a correction value by diffusing the quantization error stored in buffer, wherein the correction value to be added in

correction component is generated by error diffusion component from the quantization errors of neighboring pixels of the target pixel stored in buffer and diffusion coefficients being smaller than 1.0.

In response: Katayama discloses a bit connection component (e.g., a program storing in the ROM 912 for executing adding pixel data to error data (a bit connection), block S3, figure 28, column 20, lines 4-6) that connects a decimal portion of corrected image data (e.g., a distribution-error value (decimal portion), column 20, lines 36-37) of a preceding pixel (e.g., objective pixel, column 20, lines 44-46) output from a latch component (e.g., error storing means block 908, figure 25), to image data of a target pixel as lower bits of the image data of the target pixel (e.g., a neighboring pixel (a target pixel), column 20, lines 44-48), and outputs the bit-connected image data of the target pixel, wherein the bit-connected image data has an integer portion of the image data of the target pixel and the decimal portion of image data of the preceding pixel (e.g., when the objective pixel is input (the image inputting means 901 and the image inputting section 914), the density of the objective pixel is added to the error data (stored in the image memory 915) which was previously accumulated in (distributed to) the objective pixel position (data adding means), column 20, lines 25-31); a correction component (e.g., data adding means block 902, error-to-be-distributed computing means block 903, and error storing means block 908, figure 25) that generates corrected image data of the target by adding a correction value to the bit-connected image data of the target pixel (e.g., figure 25, column 19, lines 44-65); the latch component (e.g., arithmetic error computing means 905; error distributing means 907,

figure 25) that latches the a decimal portion of the corrected image data of the target pixel to be connected to image data of a next pixel (e.g., arithmetic-error computing means 905 for computing an arithmetic error from a signal from the data adding means 902 and a signal output from the error-to-be-distributed computing means 904, column 19, lines), without latching an integer portion of the corrected image data of the target pixel (e.g., error-to-be-distributed computing means 904 for performing integral operations (with a decimal portion omitted), column 19, lines 49-50. Note: error-to-bedistributed computing means 904 for performing integral operations (separated from decimal portion); a quantization component that receives an integer portion of the corrected image data without receiving the decimal portion of the corrected image data of the target pixel, and quantizes the received integer portion of the corrected image data of the target pixel (e.g., error-to-be-distributed computing means 904 for performing integral operations (with a decimal portion omitted), column 19, lines 47-50); a buffer that stores the calculated quantization error (e.g., error distributing means 907 and block 908, figure 25); and an error diffusion component that generates a correction value by diffusing the quantization error stored in buffer (e.g., error storing means block 908 and data adding means block 902, figures 25), wherein the correction value to be added to the bit connected image data of the target pixel in correction component is generated by error diffusion component based on the calculated quantization errors of neighboring pixels of the target pixel stored in buffer and diffusion coefficients being smaller than 1.0 (e.g., figure 27 with diffusion coefficient 1/3, 1/6 added to objective pixel,...column 20, lines 23-35).

Katayama does not explicitly disclose an inverse quantizing component that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel, and outputs an inverse-quantized data of the target pixel; a calculation component that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel.

Ishikawa's 075 discloses an inverse quantizing component (e.g., inverse quantizer 31, figure 3) that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel (e.g., output from quantizer 13 (integer portion), figure 3), and outputs an inverse-quantized data of the target pixel (e.g., the quantized representative values of the CMY signals outputted by the inverse quantizer 31, column 8, lines 19-21); a calculation component (e.g., The adder/subtractor 32, column 8, line 18) that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel (e.g., subtracting the CMY signals outputted by the offset adder 17, column 8, lines 18-19) and the inverse-quantized data (e.g., the quantized representative values of the CMY signals outputted by the inverse quantizer 31, column 8, lines 19-21).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have modified Katayama to include an inverse quantizing component that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel, and outputs an inverse-quantized data of the target pixel; a calculation

component that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel as taught by Ishikawa's 075. It would have been obvious to one of ordinary skill in the art at the time of the invention to have modified Katayama by the teaching of Ishikawa to conveniently diffuse error to neighboring pixels to have better image quality.

## Claim Rejections - 35 USC § 101

35 U.S.C. 101 reads as follows:

Whoever invents or discovers any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof, may obtain a patent therefor, subject to the conditions and requirements of this title.

Claim 39 is rejected under 35 U.S.C. 101 because the claimed invention is directed to non-statutory subject matter. Claim 39 is drawn to functional descriptive material NOT claimed as residing on a non-transitory computer readable medium.

MPEP 2106.IV.B.1 (a) (Functional Descriptive Material) states:

"Data structures not claimed as embodied in a non-transitory computer-readable medium are descriptive material per se and are not statutory because they are not capable of causing a long lasting functional change in the computer."

"Such claimed data structures do not define any structural or functional interrelationships between the data structure and other claimed aspects of the invention which permit the data structure's functionality to be realized."

Claim 39, while defining computer-readable medium, does not define a "non-transitory computer-readable medium" and is thus non-statutory for that reasons. A medium can range from signal to paper on which the medium is written.

# Claim Rejections - 35 USC § 103

The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.

Claims 1, 3, 7, 20, 22, 26, and 39 are rejected under 35 U.S.C. 103(a) as being unpatentable over Katayama et al. (Katayama) (US 5,488,673) in view of Ishikawa (US 6,330,075).

With regard to claim 1, Katayama discloses an image processing apparatus (see Katayama, e.g., an image processing apparatus, figure 26) for quantizing input image data (e.g., binarizing means 903, Fig. 25), comprising: a bit connection component (e.g., a program storing in the ROM 912 for executing adding pixel data to error data (a bit connection), block S3, figure 28, column 20, lines 4-6) that connects a decimal portion of corrected image data (e.g., a distribution-error value (decimal portion), column 20, lines 36-37) of a preceding pixel (e.g., objective pixel, column 20, lines 44-46) output from a latch component (e.g., error storing means block 908, figure 25), to image data of a target pixel as lower bits of the image data of the target pixel (e.g., a neighboring pixel (a target pixel), column 20, lines 44-48), and outputs the bit-connected image data of the target pixel, wherein the bit-connected image data has an integer portion of the image data of the target pixel and the decimal portion of image data of the preceding pixel (e.g., when the objective pixel is input (the image inputting means 901 and the image inputting section 914), the density of the objective pixel is added to the error data

(stored in the image memory 915) which was previously accumulated in (distributed to) the objective pixel position (data adding means), column 20, lines 25-31); a correction component (e.g., data adding means block 902, error-to-be-distributed computing means block 903, and error storing means block 908, figure 25) that generates corrected image data of the target by adding a correction value to the bit-connected image data of the target pixel (e.g., figure 25, column 19, lines 44-65); the latch component (e.g., arithmetic error computing means 905; error distributing means 907, figure 25) that latches the a decimal portion of the corrected image data of the target pixel to be connected to image data of a next pixel (e.g., arithmetic-error computing means 905 for computing an arithmetic error from a signal from the data adding means 902 and a signal output from the error-to-be-distributed computing means 904, column 19, lines), without latching an integer portion of the corrected image data of the target pixel (e.g., error-to-be-distributed computing means 904 for performing integral operations (with a decimal portion omitted), column 19, lines 49-50. Note: error-to-bedistributed computing means 904 for performing integral operations (separated from decimal portion); a quantization component that receives an integer portion of the corrected image data without receiving the decimal portion of the corrected image data of the target pixel, and quantizes the received integer portion of the corrected image data of the target pixel (e.g., error-to-be-distributed computing means 904 for performing integral operations (with a decimal portion omitted), column 19, lines 47-50); a buffer that stores the calculated quantization error (e.g., error distributing means 907 and block 908, figure 25); and an error diffusion component that generates a correction

value by diffusing the quantization error stored in buffer (e.g., error storing means block 908 and data adding means block 902, figures 25), wherein the correction value to be added to the bit connected image data of the target pixel in correction component is generated by error diffusion component based on the calculated quantization errors of neighboring pixels of the target pixel stored in buffer and diffusion coefficients being smaller than 1.0 (e.g., figure 27 with diffusion coefficient 1/3, 1/6 added to objective pixel,...column 20, lines 23-35).

Katayama does not explicitly disclose an inverse quantizing component that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel, and outputs an inverse-quantized data of the target pixel; a calculation component that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel.

Ishikawa's 075 discloses an inverse quantizing component (e.g., inverse quantizer 31, figure 3) that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel (e.g., output from quantizer 13 (integer portion), figure 3), and outputs an inverse-quantized data of the target pixel (e.g., the quantized representative values of the CMY signals outputted by the inverse quantizer 31, column 8, lines 19-21); a calculation component (e.g., The adder/subtractor 32, column 8, line 18) that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel (e.g., subtracting the CMY signals outputted by the

offset adder 17, column 8, lines 18-19) and the inverse-quantized data (e.g., the quantized representative values of the CMY signals outputted by the inverse quantizer 31, column 8, lines 19-21).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have modified Katayama to include an inverse quantizing component that inverse-quantizes the quantized integer portion of the corrected image data of the target pixel, and outputs an inverse-quantized data of the target pixel; a calculation component that outputs a quantization error of the target pixel based on a difference between the integer portion of the corrected image data of the target pixel and the inverse-quantized data of the target pixel as taught by Ishikawa's 075. It would have been obvious to one of ordinary skill in the art at the time of the invention to have modified Katayama by the teaching of Ishikawa to conveniently diffuse error to neighboring pixels to have better image quality.

With regard to claim 3, Katayama discloses further comprising a stop component that stops propagating the correction value in a case in which it is inappropriate to propagate the correction value to next and subsequent pixels (e.g., the error distribution controlling circuit, figures 6, column 7, line 61 – column 8, lines 63).

With regard to claim 7, Katayama discloses further comprising a numerical value limit component that limits the quantization error calculated by calculation component to a numerical value within a predetermined range (e.g., the error distribution controlling circuit, column 7, line 61 – column 8, line 65).

#### Referring to claim 20:

Claim 20 is the method claim corresponding to operation of the device in claim 1 with method steps corresponding directly to the function of device elements in claim 1.

Therefore claim 20 is rejected as set forth above for claim 1.

### Referring to claim 22:

Claim 22 is the method claim corresponding to operation of the device in claim 3 with method steps corresponding directly to the function of device elements in claim 3. Therefore claim 22 is rejected as set forth above for claim 3.

### Referring to claim 26:

Claim 26 is the method claim corresponding to operation of the device in claim 7 with method steps corresponding directly to the function of device elements in claim 7.

Therefore claim 26 is rejected as set forth above for claim 7.

### Referring to claim 39:

Claim 39 is the computer-executable storage medium claim corresponding to operation of the device in claim 1 with instruction steps corresponding directly to the function of device elements in claim 1. Therefore claim 39 is rejected as set forth above for claim 1.

Claims 4-6, and 23-25 are rejected under 35 U.S.C. 103(a) as being unpatentable over Katayama et al. (Katayama) (US 5,488,673) and Ishikawa (US 6,330,075) as applied to claims 1 and 3 above, and further in view of Nakano et al. (Nakano) (US 6,977,756).

With regard to claim 4, Katayama and Ishikawa's 075 differ from claim 4, in that they do not explicitly show a clear component to clear data/error portion in latch/temporary memory in case in which it is inappropriate.

Nakano discloses a clear component to clear data/error portion in latch/temporary memory (e.g., it clears a content of the error holding register, column 5, lines 58-61).

Therefore it would have been obvious to one of ordinary skill in the art at the time of the invention to have modified Katayama and Ishikawa's 075 to include a clear component to clear data/error portion in latch/temporary memory in case in which it is inappropriate conditions as taught by Nakano. It would have been obvious to one of ordinary skill in the art at the time of the invention to have modified Katayama and Ishikawa's 075 by the teaching of Nakano to clear data/error as needed.

With regard to claim 5, Nakano discloses further comprising a processing limit component that limits clearing by clear component when a scanning direction of the input image is reversed (e.g., adder 9 detects forward and reversed direction, column 9, lines 13-34).

With regard to claim 6, Nakano discloses wherein the case in which it is inappropriate to propagate the correction value to next and subsequent pixels includes at least one of a case in which a pixel of interest is a start pixel of a line, a case in which the pixel of interest has a value equal to a lower limit level of the input image, and a case in which the pixel of interest has a value equal to an upper limit level of the input image (column 8, line 48 – column 9, line 3).

### Referring to claim 23:

Claim 23 is the method claim corresponding to operation of the device in claim 4 with method steps corresponding directly to the function of device elements in claim 4.

Therefore claim 23 is rejected as set forth above for claim 4.

#### Referring to claim 24:

Claim 24 is the method claim corresponding to operation of the device in claim 5 with method steps corresponding directly to the function of device elements in claim 5.

Therefore claim 24 is rejected as set forth above for claim 5.

# Referring to claim 25:

Claim 25 is the method claim corresponding to operation of the device in claim 6 with method steps corresponding directly to the function of device elements in claim 6.

Therefore claim 25 is rejected as set forth above for claim 6.

#### Conclusion

THIS ACTION IS MADE FINAL. Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of

the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to Quang N. Vo whose telephone number is (571)270-1121. The examiner can normally be reached on 7:30AM-5:00PM Monday-Friday.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David K. Moore can be reached on (571)272-7437. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/Quang N Vo/ Examiner, Art Unit 2625

/David K Moore/

Supervisory Patent Examiner, Art Unit 2625